

Electric/Magnetic Antenna

Electric Antenna (fast/slow)

Shape: semi-sphere

Receivable frequency bandwidth: 1kHz to 5MHz (fast)
0.1Hz to 100kHz (slow)

Capacitance: 10 to 30pF

Gain: 40dB

Outer diameter: 250mm

Height: 2500mm

Insulated stand will be supplied

Cable: 5D2V connector on both ends, 20m



Magnetic Loop Antenna (NS-EW, 2channels)

Dimension: sphere

Directional: orthogonal 2 directions (NS/EW, 2ch)

Receivable frequency bandwidth: 1kHz to 5MHz

N: 2 turns

Outer diameter: 600mm

Height: 2500mm

Insulated stand will be supplied

Cable: 5D2V connector on both ends, 20m



 **Lightning measurement**

Distributed by M Square, Corp.

1-34 Kanda-Jimbocho, Chiyoda-ku Tokyo 101-0051 Japan

Tel : 81-3-5962-8548 Fax: 81-3-6856-4866

<http://www.lightning-measurement.com/> info@lightning-measurement.com/

Manufacturer: Photonics Co., Ltd.

1-19-38 Hon-Machi, Higashi-Murayama Tokyo 189-0014 Japan

pho@poppy.ocn.ne.jp